

## THERMOMASTER W-PROF

### Connecting profile to frame

|                  |   |
|------------------|---|
| Product:         | Connecting profile to frame   |
| Supplier:        | MASTERPLAST Kft., 8143 Sárszentmihály, Árpád u. 1/a.<br>(www.masterplastgroup.com)  |
| Size, packaging: | 2,5m*20pcs - 50m/bundle   |
| Application:     | Applied for exact connections to soffits with insulation systems. The self-adhesive silicone strip ensures the flexible, water-tight cooperation with the windowframe and the fiberglass mesh the connection to the rendering. The removable plastic part with adhesive strip ensures the fixing of the protective covering of glass during plastering. |
| Material:        | Extruded PVC profile with watertight, closed cell siliconefoam stripe and fiberglass mesh.  |

| Properties                        | Relevant standards                  | Technical data       |
|-----------------------------------|-------------------------------------|----------------------|
| Length of profile                 | Manufacturer's declared value (MDV) | 250cm                |
| Width of profile                  | MDV                                 | 9 mm                 |
| Unit weight of profile            | MDV                                 | 55 g/fm              |
| Width of siliconefoam stripe      | MDV                                 | 8mm                  |
| Thickness of siliconefoam stripe  | MDV                                 | 3mm                  |
| Width of fiberglass               | MDV                                 | 10 cm                |
| Unit weight of fiberglass         | MDV                                 | 125 g/m <sup>2</sup> |
| Width of removable plastic stripe | MDV                                 | 15mm                 |
| Temperature of application        | MDV                                 | min. (+) 5°C         |

**Storage and handling**

Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources as well as against moisture and rain.

**Guarantee, warranty:**

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims.

**Standards, specifications**

ETAG 004

**Health and safety**

No labelling required in accordance with the relevant regulation (EC) No. 1907/2006 of the European Parliament and of the Council (REACH).

This datasheet corresponds to our current knowledge, experiences and general informations on the subject, but may be revised as new knowledge and/or experience becomes available. It does not imply any legally binding assurance. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

**This technical datasheet is applied to products sold by Masterplast Kft. and valid until withdrawal or until modification.** Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (\*see date of issuing).

Most recent version of this datasheet can be also accessed under [www.masterplastgroup.com](http://www.masterplastgroup.com). Modification of this technical datasheet repeals the previously issued version!