

Thermomaster Primer

Product:	Thermomaster Primer	
Distributor:	MASTERPLAST Kft., 8143 Sárszentmihály, Árpád u. 1/a	
Size, packaging:	1 l/pail or 5 l/pail	
Application:	For equalizing of the different water-absorption ability of the base surface, increasing of the adhesion ability. Applicable under tile adhesives, self-levelling compounds, plasters.	
Material:	Acrylate copolymer, water, surfactants.	

General properties	Test method	Technical data
Density	Manufacturer's declared value (MDV)	~ 1,02 g/cm ³
Application	MDV	textile paint roller , painting brush
Temperature conditions - surface and air	MDV	between (+)5 °C - (+)25 °C
Consumption (depending on the water absorption and roughness of the surface)	MDV	0,1 – 0,15 l/m ²
Dilution (depending on the surface)	MDV	1:1 – 1:3 (primer:water)
Drying time (+20 °C, r. h. 65 %)	MDV	~ 2 hours (touch dry)
	MDV	~ 5 hours (suitable for the next layer)
Resistance to precipitation (washing away of the application) (+20 °C, r. h. 65 %)	MDV	~ 24 hours

Storage and handling

In case of the prescribed storage and handling conditions, the expiry date of the product is 12 months after production (in properly closed plastic pail, under dry conditions, protected against atmospheric exposure, especially sun-radiation and freeze. Storing temperature is between (+)5°C and (+)25°C).

Guarantee, warranty:

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims. Preparation of a test surface at the building site is advised before applying the product onto the whole surface.

Health and safety

No labelling required in accordance with the relevant regulation (EC) No. 1272/2008 of the European Parliament and of the Council.

This datasheet corresponds to our current knowledge, experiences and general informations on the subject, but may be revised as new knowledge and/or experience becomes available. It does not imply any legally binding assurance. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

This technical datasheet is applied to products sold by Masterplast Kft. and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com. Modification of the technical datasheet repeals the previously issued versions!