





























COLORI / COLORS



Esempio di applicazione




SCHEDA ORDINE PRODOTTO / PRODUCT ORDER DATA SHEET

COD.	MOD.							
GIUNTO7X8-01	8x8mm			2m	100m	11200m	110x200x60	0,081 kg/m
GIUNTO8X8-02	8x8mm			2m	100m	11200m	110x200x60	0,081 kg/m
GIUNTO9X8-01	10x8mm			2m	100m	9100m	110x200x60	0,090 kg/m
GIUNTO9X8-02	10x8mm			2m	100m	9100m	110x200x60	0,090 kg/m
GIUNTO11X8-01	12x8mm			2m	100m	8400m	110x200x60	0,094 kg/m
GIUNTO11X8-02	12x8mm			2m	100m	8400m	110x200x60	0,094 kg/m
GIUNTO13X8-01	14x8mm			2m	100m	5500m	110x200x60	0,111 kg/m
GIUNTO13X8-02	14x8mm			2m	100m	5500m	110x200x60	0,111 kg/m
GIUNTO16X8-01	16x8mm			2m	100m	5000m	110x200x60	0,122 kg/m
GIUNTO16X8-02	16x8mm			2m	100m	5000m	110x200x60	0,122 kg/m

*MEASURES IN CENTIMETERS

SCHEDA TECNICA PRODOTTO / TECHNICAL SHEET

MOD.	S*	B*	H*
8x8mm	8,2	15	8,2
10x8mm	8,2	15	10,4
12x8mm	8,2	15	12,4
14x8mm	8,2	15	14,1
16x8mm	8,2	15	16,4



*MEASURES IN MILLIMETERS - TOLERANCE ±4%

GIUNTO DI DILATAZIONE

Prodotto da GRUPPO STAMPLAST è in grado di prevenire il distacco della mattonella in seguito ad assestamenti delle strutture portanti o al ritiro del cemento durante il processo di maturazione. Il suo utilizzo è particolarmente indicato per pavimentazioni industriali e di grandi misure. Il giunto di dilatazione è indicato solo per uso interno.

Materiale: PVC rigido in coestrusione con PVC morbido.

EXPANTION JOINT

Manufactured by GRUPPO STAMPLAST, it prevent the detachment of the tile after settling of the supporting structures or to the shrinkage of the cement during the process of maturation. Its use is particularly suitable for industrial flooring and large size floors.

The expansion joint is suitable for indoor use only.

Material: Rigid PVC co-extruded with soft PVC.