






COLORI / COLORS



SCHEDA ORDINE PRODOTTO / PRODUCT ORDER DATA SHEET



COD.	MOD.	↔					
DL15-01	H15mm	2m	A	100	8800	100x200x120	0,085 kg/m
DL15-01A	H15mm	1m	A	50	4500	100x100x120	0,085 kg/m
DL20-01	H20mm	2m	A	100	6300	100x200x120	0,120 kg/m
DL20-01A	H20mm	1m	A	50	2950	100x100x120	0,120 kg/m
DL25-01	H25mm	2m	A	100	5600	100x200x120	0,138 kg/m
DL25-01A	H25mm	1m	A	50	2600	100x100x120	0,138 kg/m
DL30-01	H30mm	2m	A	100	4900	100x200x120	0,165 kg/m
DL30-01A	H30mm	1m	A	50	2300	100x100x120	0,165 kg/m
DL35-01	H35mm	2m	C	64	3136	100x200x120	0,186 kg/m
DL35-01A	H35mm	1m	C	32	1568	100x100x120	0,186 kg/m
DL40-01	H40mm	2m	B	60	2700	100x200x120	0,215 kg/m
DL40-01A	H40mm	1m	B	32	1344	100x100x120	0,215 kg/m
DL50-01	H50mm	2m	B	64	1920	100x200x120	0,270 kg/m
DL50-01A	H50mm	1m	B	32	960	100x100x120	0,270 kg/m

*MEASURES IN CENTIMETERS

SCHEDA TECNICA PRODOTTO / TECHNICAL SHEET

MOD.	L*	H*
H15mm	30	15
H20mm	30	20
H25mm	30	25
H30mm	30	30
H35mm	30	35
H40mm	42	40
H50mm	42	50

*MEASURES IN MILLIMETERS



RINFORZO CALCESTRUZZO

DISTANZIATORE LINEARE

Prodotto da GRUPPO STAMPLAST ha un profilo ad U molto robusto, è molto resistente alla compressione, è di semplice posa ed è indicato per armature orizzontali, verticali o inclinate. Inoltre la presenza di fori sui tre lati consentono una penetrazione uniforme del calcestruzzo.

Materiale: PVC estruso.

LINEAR SPACER

Manufactured by GRUPPO STAMPLAST it features a U-shaped strong lateral profile ensuring high-load bearing capacity. It's easy to install and suitable for horizontal, vertical or inclined reinforcement. Moreover, the lateral cut-outs allow an easy and uniform penetration of the concrete.

Material: Extruded PVC.